THE FIRECHECK TANK Steel Outer, Plastic Inner



Fitted with locking

point

Now there is a product available which is a real step forward in fire rated tanks... **The Envirostore Firecheck Tank**. With a combination of the strength and security of steel, the practicality of a plastic bunded inner tank, and the protection of a fire rated material, all giving peace of mind to the installer.

All Firecheck Date conduction In accordance In the BSSall In accordance In the BSSall In accordance In a

Example of low profile option

NEW

The inner area of the tank is clad in a 30 minute fire rated material, then completely enclosed in a mild steel outer tank, making the unit weatherproof and secure.



Members of

THE FIRECHECK TANK Steel Outer, Plastic Inner

A horizontal Bunded Tank complete with the unique Envirostore inner spill tray design (fuel overfill cannot come into contact with fire material). No additional fire walls need be provided, so no more unsightly additional brick or block walls adding extra cost to the installation (a risk assessment will still need to be carried out).

1000 EHFC

30 min fre rated material

Brimful	1 080 litres
Nominal	1026 litres
Length	2100 mm
Width	780 mm
Height	1625 mm
Footprint	2100 mm x 780 mm
Weight	560kgs

1300 EHFC 1 400 litres Brimful Nominal 1330 litres 1930 mm Length 1400 mm Width 1620 mm Height Footprint 1930 mm x 1400 mm Weight 710kgs


1225 EHFC Brimful 1270 litres Nominal | 206 litres Length 2160 mm Width 960 mm Height 1820 mm Footprint 2160 mm x 960 mm Weight 605kgs

1800 EHFC 1910 litres Brimful Nominal 1814 litres Length 2170 mm 1425 mm Width Height 1720 mm Footprint 2170 mmx 1425 mm Weight 770kgs

1250 ELPFC		
Brimful	1330 litres	
Nominal	1206 litres	
Length	2070 mm	
Width	1510 mm	
Height	1250 mm	
Footprint	2070 mm x 1510 mm	
Weight	760kgs	

2500 EHFC

2625 litres Brimful Nominal 2493 litres Length 2330 mm 1630 mm Width 1820 mm Height Footprint 2330 mmx 1630 mm Weight 870kgs



Tanks come fitted with 76mm high channels running lengthways across the bottom as standard to allow air to circulate underneath.



All fittings are accessed via a secure, fire protected lockable lid.

- Apollo visual contents gauge
- Fittings kit for bottom outlet supplied as standard. Top outlet available upon request
- Overfill limiter device

- Painted green as standard other colours available if required at extra cost
- Tin of touch up paint provided as standard

Envirostore accept liability for the replacement of faulty tanks, but accept no liability for loss of fuel and/or environment or property damage due to spillage of fuel from a Single Skin Tank. BS5410 Standard requires a fuel tank to have a 20 year life expectancy and this confirms the need to fit an Envirostore Bunded Tank.

Suitable access is required for delivery and may be on an artic vehicle. Delivery point must have suitable off-loading facilities available. Tail lift to ground level may be available if required and please specify when ordering.

Delivery times can vary on larger capacity tanks, please check before ordering. Allow up to 21 days for delivery.

Stockist



the tank specialists

Poly-Roto Centre 10 Tinure Business Park, Tinure, Drogheda, Co. Louth, Ireland

UK Sales: 07540 299 917 Tel: 00353 41 686 2968

Email: envirostore@yahoo.co.uk

www.envirostoreuk.com

A risk assessment still needs to be carried out by an OFTEC registered installer. The product does not prevent fires from starting, caution and care around the tank with regards to garden fires, BBQ's etc should still be taken. This product should only be lifted using the appropriate lifting equipment.

All tanks must be fitted by an OFTEC registered or an equal and approved Engineer. The Envirostore Warranty may be affected if not installed correctly, or if any unauthorised work has been carried out on the tank, without the knowledge or permission of Envirostore UK Ltd. For details on the current regulations, consult an OFTEC registered or an equal and approved Engineer. The Inner Spill Tray must be kept clean and dry at all

times. Locks need to be kept in good working order and can be maintained by using WD40 or 3 in I oil.

All Bunded Tanks have a 20 year life expectancy. Fuel Dispensers and Waste Oil Tanks carry a 5 year warranty. Single Skin Tanks, including Water Tanks, carry a 2 year warranty. Lumps on Fuel Dispensers, Filstops, Locks, Hinges and Fitting Packs carry a 1 year warranty. Hoses on Fuel Dispensers carry a 3 month warranty. For details of warranty on Gauges, please consult the appropriate gauge manufacturers details separately

Dimensions shown are approximate. Capacity details shown as Brimful and Nominal. Patent pending on Inner Spill Tray